

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

# Soild Door Freezer

Reach-In Top Mounts M3 Series

### \_\_\_ FEATURES / BENEFITS =\_\_

## Model: M3F72-3

#### ■ DIGITAL TEMPERATURE CONTROL SYSTEM

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

#### High-Tech Monitor

The monitor digitally displays the present temperature. You can easily change the temperature by adjusting the thermostat.

#### ■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### ■ EFFICIENT REFRIGERATION SYSTEM

M3's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

#### AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the freezer door opens, the circulation of hot, moist air into the freezer is prevented. This increases energy efficiency and lengthens the life of the compressor.

#### ■ ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) **COATED WIRE SHELVES**

#### STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air M3 freezer model boasts a stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The M3 can add a touch of style to the most refined setting.

#### ■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

## ■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

#### ■ TOP MOUNT COMPRESSOR UNITS

The refrigeration systems are designed to ensure that each part is properly sized and balanced to achieve the highest efficiency and performance.



FREEZER HOLDS -10°F ~ 0°F FOR THE BEST IN FROZEN FOOD PRESERVATION













**ENERGY STAR®** Qualified

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
M3F72-3	3	72	9	11/4	10.4	571	773/4 x 303/4 x 78

(unit: inch)

# Soild Door Freezer

## **Model: M3F72-3**

ELECTRICAL DATA					
Voltage ‡	115/208~230/60/1				
Plug Type <sup>‡</sup>	○ NEMA-L14-20				
Full Load Amperes	10.4				
Compressor HP	11/4				
Feed Wires with Ground	4				
Cord Length ft.	9				
Refrigerant	R-404A				
DIMENSIONAL DATA					
# of Doors	3				
# of Racks Accepted	3				
Net Capacity cu. ft.	72				
Ext. Length Overall in.	773/4 (1975mm)				
Ext. Depth Overall in.*	30 <sub>3/4</sub> (781mm)				
Ext. Height Overall in.†	78 (1981mm)				
Int. Length Overall in.	737/8 (1877mm)				
Int. Depth Overall in.	245/8 (625mm)				
Int. Height Overall in.	605/8 (1539mm)				
Gross Weight lbs.	571				
# of Shelves	9				
Shelf Size (LxD) in.	231/2x251/4 231/2x231/8 231/2x251/4				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- \* Depth does not include 1-3/8" for rear condensate enclosure.
- † Height does not include 5" for caster height.
- ‡ M3F72-3 requires 115/208-230/60Hz, single phase, 3 pole, 4 wire circuit. (NEMA-L14-20)


## ■ WARRANTY: 2 Year Parts and Labor Warranty **Additional 3 Year Warranty on Compressor**

- INCANDESCENT INTERIOR LIGHTING
- MINIMUM WATTAGE HEATER IN CABINET FRAME
- Door Locks
- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- SOLID AND STURDY GRILLE DESIGN
- TRAY RACK AVAILABLE (OPTIONAL)


#### ■ OPTIONAL ACCESSORIES:

- ☐ 5" Diameter swivel casters
- ☐ 6" Standard legs
- Additional PE coated wire shelves
- ☐ Half door bun tray racks. Each holds up to seven 18"Lx26"D sheet pans (sold separately)
- ☐ Full door bun tray racks. Each holds up to fifteen 18"Lx26"D sheet pans (sold separately)

### **PLAN VIEW**



**PLAN VIEW** 



SIDE VIEW











**ENERGY STAR®** Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002







Ver.201304



