

☀ Features & Benefits

- This best selling 2 x 1.5 gallon size meets the rigorous demands of medium-to-large sized operations.
- Designed for simplicity, the Handle Operated series brewers save operator time and effort by delivering consistent results from your pre-programmed coffee recipe.
- Twin station configuration provides the flexibility of brewing two different recipes or into two different types of dispensers at the same time!
- Twin 1.5 gallon brewer is a popular choice across many segments due to its speed, capacity and reliable performance during peak service times.
- Brew directly into our best-selling LUXUS® L3D series dispensers or try the ultra durable TPD series thermal dispensers and extend your beverage service capabilities (sold separately).
- Available in multiple power configurations to efficiently meet your cups-per-hour requirement and keep energy costs at a minimum.



⚡ Electrical Configuration

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon/Hour
US / CANADA								
C52016	2 x 3.0 kW	120/208-240	1	3+G	4.6-6.1	Hardwired	22.0-25.4	10.5-15.0 ⁽¹⁾
C52026	2 x 4.0 kW	120/208-240	1	3+G	6.1-8.1	Hardwired	29.3-33.8	15.0-19.5 ⁽¹⁾
C52036 ⁽²⁾	3 x 3.0 kW	120/208-240	3	4+G	7.0-9.1	Hardwired	19.5-22.4	16.5-22.5 ⁽¹⁾
C52046 ⁽²⁾	3 x 4.0 kW	120/208-240	3	4+G	9.1-12.1	Hardwired	25.6-29.6	22.5-30.0 ⁽¹⁾
C52186 ⁽²⁾	3 x 4.0 kW	440-480	3	3+G	10.3-12.1	Hardwired	13.6-14.8	22.5-30.0 ⁽¹⁾
EXPORT								
C52076 ⁽²⁾	3 x 3.0 kW	220-240/380-415	3	4+G	7.8-9.1	Hardwired	11.8-12.9	19.5-22.5 ⁽¹⁾
C52086 ⁽²⁾	3 x 4.0 kW	220-240/380-415	3	4+G	10.3-12.1	Hardwired	15.7-17.1	25.5-30.0 ⁽¹⁾
C52096 ⁽²⁾	2 x 3.0 kW	220-240	1	2+G	5.1-6.1	Hardwired	23.3-24.4	13.5-15.0 ⁽¹⁾
C52106 ⁽²⁾	2 x 4.0 kW	220-240	1	2+G	6.8-8.1	Hardwired	30.9-33.8	18.0-19.5 ⁽¹⁾

(1) Based on standard factory settings: 4.0 minute brew time; 0% prewet; 200°F water.
 (2) Requires 3 phase upcharge (Z056).

💧 Water Specification

Water Inlet	Water Pressure	Minimum Flow Rate
3/8" Male Flare	20-75 psig	1 1/4 gpm

↔ Dimensions

Type	Height	Width	Depth	Weight
Product	36"	21"	20"	82 lbs
Shipping	35"	23"	23"	100 lbs

🛒 Customize Your Brewer

DISPENSERS

- 1.5 Gallon Thermal Server (L3S-15) **D052**
- 1.5 Gallon Thermal Dispenser (L3D-15) **D049**
- 1.5 Gallon Thermal Dispenser (TPD-15) **D009**



L3S-15 Thermal Server



L3D-15 Thermal Dispenser



TPD-15 Thermal Dispenser

ACCESSORIES

- Single Serving Station for L3S-15/20 Server **A097**
- Twin Serving Station for L3S-15/20 Server **A098**
- Triple Serving Station for L3S-15/20 Server **A099**
- Quad Serving Station for L3S-15/20 Server **A129**
- Identifier Plates, Acrylic **A069**
- Hot Tea Infuser (1.5 Gallon Size) **A113**
- Drip Tray - Square **A137**
- Iced Tea Brew Basket (16" x 6") **B001110G1**
- Half Batch Brew Basket Assembly w/ Black Handle **B004280B1**
- for CBS-5000 Series Brewers (13" x 5" with .280 Drip Hole)

OPTIONS

- Orange Dispenser Faucet Replacement Handle **1071.00029.00**
- Green Dispenser Faucet Replacement Handle **1071.00031.00**
- Blue Dispenser Faucet Replacement Handle **1071.00032.00**

WATER FILTRATION SYSTEM

- In-Line Water Filter (Head / Cartridge / Hose) **A039**
- Replacement Water Filter Cartridge **A075**

PAPER COFFEE FILTERS

- 15" x 5 1/2" (500/Case) **F001**