

Heater Proofer - Non-Insulated Economy **100% Pre-Tested Electrical Assembly**



- Heavy Duty, channel construction designed for durability. Easy to Clean.
- Air baffle and circulating air blower provide even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Two locking casters in front.
- Easy dual proof/heat control:
 "Proof" mode: Humidity from 30% to 95%.
 Temperatures up to 115°F (46°C)
 "Heat" mode: Nominal Temperatures up to 180°F (82°C)
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on inside door frame, held closed with magnets, Lexan fits tightly into door frame.
- Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- All controls are accessible without opening cabinet door.
- Easy to read LED thermometer.
- Pan Capacity: 36 - 18" x 26" pans

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



NHP-PD-ECO
 Removable Drawer
 Makes Cleaning Quick & Easy

On Both NHPL-1836-ECO &
 NHPL-1836 Units

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1836-ECO	637795	21	533	30¾	781	68	1,727	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

For replacement parts
 please see page 125.

Freight Class: 100



Air baffle and circulating air blower
 provide even heat distribution.



Heater Proofer - Non-Insulated Standard

100% Pre-Tested Electrical Assembly

- Heavy Duty, channel construction designed for durability. Easy to Clean.
- Air baffle and circulating air blower provide even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Two locking casters in front.
- Easy dual proof/heat control:
 - "Proof" mode: Humidity from 30% to 95%.
 - Temperatures up to 115°F (46°C)
 - "Heat" mode: Nominal Temperatures up to 185°F (85°C)
- Corner bumpers provide protection to unit, associates and fixtures.
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on inside door frame, held closed with magnets, Lexan fits tightly into door frame.
- Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- All controls are accessible without opening cabinet door.
- Easy to read LED thermometer.
- Pan Capacity: 36 - 18" x 26" pans



NHPL-PD-CH
Removable Drawer
Makes Cleaning Quick & Easy

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.

On Both NHPL-1836-ECO & NHPL-1836 Units



Drawer assembly view with bottom cover removed.

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1836	230421	21	533	30¾	781	68	1,727	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

Freight Class: 100

For replacement parts please see page 125.

Heater Proofer - Non-Insulated

High Performance

100% Pre-Tested Electrical Assembly



- Non-insulated - Heavy duty aluminum construction.
- Air baffle and circulating air blower provide even heat distribution.
- Higher wattage unit has quicker recovery time. Proofing/Heating module with dual elements is 120VAC, 16 AMP, cycle, 2000 watts.
- Removable chrome pan slides on 3" centers for easy cleaning.
- Clear door for easy viewing of product while retaining heating because doors are opened less. Door gasket prevents heat loss due to complete seal around the door. Field reversible door for right or left hanging standard. Magnetic door latch for keeping door closed during transport. Easy pull handle for opening.
- Easy to read LED thermometer.
- 17 pan slides hold a variety of pan configurations from sheet pans to steam table pans.
- Easy dual proof/heat control:
 - "Proof" mode: Humidity from 30% to 95%. Temperatures up to 115°F (46°C)
 - "Heat" mode: Nominal Temperatures up to 185°F (85°C)
- Drip trough catches condensation to reduce wet floor conditions. Internal water pan collects condensation or is used in proofer mode.
- 5" polyurethane plate casters standard with brakes for easy maneuverability.

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 2000 Watts: 16 AMPS



NHP-PD-HP
Removable Drawer
Makes Cleaning Quick & Easy

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1817-HP	627524	25	635	32	813	68 ^{3/4}	1,772	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

Please refer to your operational maintenance & service bulletin for replacement parts.

Freight Class: 100

Replacement drawer on page 125.



Magnetic Door Latch



Field Reversible Door Mount

Heater Proofers - Non-Insulated Universal Runner 100% Pre-Tested Electrical Assembly



- Non-insulated - Heavy duty aluminum construction.
- Air baffle and circulating air blower provide even heat distribution.
- Proofing/Heating module with dual elements is 120VAC, 14 AMP, cycle, 1220 watts. Plugs into any standard 110 outlet.
- Removable chrome pan slides for variable spacing and for easy cleaning.
- Clear door for easy viewing of product while retaining heating because doors are opened less. Door gasket prevents heat loss due to complete seal around the door. Field reversible door for right or left hanging standard. Magnetic door latch for keeping door closed during transport. Easy pull handle for opening.
- Easy to read LED thermometer.
- 25 pan slides hold a variety of pan configurations from sheet pans to steam table pans.
- Easy dual proof/heat control:
 "Proof" mode: Humidity from 30% to 95%.
 Temperatures up to 115°F (46°C)
 "Heat" mode: Nominal Temperatures up to 185°F (85°C)
- Corner bumpers provide protection to unit, associates and fixtures.
- 5" polyurethane plate casters standard with brakes for easy maneuverability.

Equipment Guide

- ✓ **BEST**
- ✓ **HEAVY DUTY USE**
- ✓ **1YR WARRANTY**
- ✓ **HACCP HELPER**
- ✓ **NSF** **UL**
- ✓ **NEW**
- ✓ **EXPRESS SHIP**



NHP-PD-UN
Removable Drawer
Makes Cleaning Quick & Easy

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



Magnetic Door Latch



Field Reversible Door Mount



Adjustable Runners

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height			
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)
NHPL-1825-UN	640067	24	610	32	813	70	1,778	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

For replacement parts please see page 125.

Freight Class: 100